


PIN1: "+极 (红色)
 PIN1: "-极 (黑色)
 PIN4: V- (黑色)
 PIN3: 信号B(蓝色)
 PIN2: 信号A(白色)
 PIN1: V+(红色或黄色)

花键有效长35
 (11) 4.5
 (10) 41.5±0.8

内花键参数表:

齿形	低齿 (正变位)
模数 m	1.0(mm)
压力角α	20°
齿数Za	18
分度圆直径	Φ18
大径	Φ19.98
小径	Φ17.8
径向变位系数	+0.8
跨测齿数R	3
公法线长度W	8.18
跨棒距M	16.067 ^{+0.071} ₀
量棒直径	Φ2
配合形式	齿侧定心

PIN NUMBER	PIN FUNCTION
SPEED SENSOR	
1	+V RED OR YELLOW
2	SIGNAL "A" WHITE
3	SIGNAL "B" BLUE
4	GROUND BLACK
THERMAL SENSOR	
1	+ RED
2	- BLACK

DWG JONES CHO	DATE	PROPRIETARY THIS TECHNICAL DATA IS PROPRIETARY TO STARS CO., LTD.	 STARS CO., LTD. TAIWAN
CHECK SHIN WANG	DATE		
APPROVED JONES CHO	DATE		
TITLE		SDK7.5-10051 AC Induction Motor	
DOCUMENT NO.		REV. 161210	
FILE:		SHEET 1 OF 1	